

**PRODUCT DATA SHEET**

Driver Phasecut 590mA 25W 18i3 male/EPN0034

Art.no: 0300-45

*Lighting Solutions*

Driver Phasecut 590mA 25W 18i3 male/EPN0034



ELECTRICAL DATA	
Protection Class (system)	1 or 2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 45
Connection 1	18i3 male
Connection 2	EPN0034 female

DRIVER	
Manufacturer (driver)	Up-Shine

**PRODUCT DATA SHEET**

Driver Phasecut 590mA 25W 18i3 male/EPN0034

Art.no: 0300-45

*Lighting Solutions*

DRIVER	
Protection Class (driver)	1 or 2
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Dimming (driver)	Phase-Cut
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - 590
CC (forward voltage driver) (V)	null - null
Max load pr circuit - B10	39
Max load pr circuit - B16	62
Max load pr circuit - C10	39
Max load pr circuit - C16	62
Max load pr circuit - C20	78
Leakage current (mA)	0.7
Inrush current time (μ s)	80.0
Inrush current I _{max} (A)	12.5

ENERGY AND CERTIFICATIONS	
CE mark	Yes