

**PRODUKTDATABLAD**

Driver Dali 700mA 30W Dali 18i5/EPN0034

Art.no: 0300-49

*Lighting Solutions*

Driver Dali 700mA 30W Dali 18i5/EPN0034



| ELEKTRISKE DATA | |
|------------------------|-----------|
| Beskyttelsesklasse | 1 or 2 |
| Dimmefunksjon (system) | DALI |
| Spenning (V) | 230V 50Hz |

| TEKNISK DATA | |
|--------------------|----------------------------|
| IP (system) | IP20 |
| Produkt Familie | Driver Dali 700mA 30W Dali |
| Utendørs | No |
| Tilkobling Kabel 1 | 18i5 DALI hann |
| Tilkobling Kabel 2 | EPN0034 hunn |

| DRIVER / BALLAST | |
|--------------------|------|
| Produsent (driver) | Boke |

**PRODUKTDATABLAD**

Driver Dali 700mA 30W Dali 18i5/EPN0034

Art.no: 0300-49

*Lighting Solutions*

| DRIVER / BALLAST | |
|--|----------------------|
| Effekt (driver) (W) | 30 |
| Beskyttelsesklasse (driver) | 2 |
| Standbyeffekt Psb (W) < | 0.5 |
| Flimmerindikator (Pst LM) < | 1.0 |
| Stroboskopeffektindikator (SVM) < | 0.4 |
| Maks utgangsspenning (V) | 42 |
| Dimmefunksjon (driver) | DALI2 |
| Minimum dimmenivå (%) | 1.0 |
| Type Dimming | Amplitude Modulation |
| IP-klasse (driver) | IP20 |
| Forventet levetid (driver) (t) | 100000 |
| Konstant strøm eller spenning (CC eller CV) | CC |
| Konstant strøm (CC driver) (mA) | 300 - 750 |
| Konstant strøm (CC driftspenning driver) (V) | 6.0 - 42.0 |
| Konstant spenning (CV driver) (V) | 33 |
| Utgangsstrøm toleranse (%) | 5.0 |
| Strømkrusning (%) | 5.0 |
| Maks belastning per kurs - B10 | 48 |
| Maks belastning per kurs - B16 | 77 |
| Maks belastning per kurs - C10 | 48 |
| Maks belastning per kurs - C16 | 77 |
| Maks belastning per kurs - C20 | 96 |
| Maks belastning per kurs - C25 | 120 |
| Lekkasjestrøm (mA) | 0.7 |
| Startstrøm tid (μ s) | 194.0 |
| Startstrøm I _{max} (A) | 6.5 |

| ENERGI OG GODKJENNING | |
|-----------------------|-----|
| CE-merke | Yes |