



**PRODUCT DATA SHEET**

Panel 595x595 5000lm 930 36W Prism BK EPN0024 w/o driver

Art.no: 0388-02-2

*Lighting Solutions*

Panel 595x595 5000lm 930 36W Prism BK EPN0024 w/o driver



LED Panel with black frame and micro prismatic diffuser. Constructed for fitting in to suspended ceilings. Panel LED's can be installed as a pendant or mounted on ceiling surfaces Choose between on/off, phasecut or DALI2 (CLO, Corridor, Push dim and Ready2mains) driver.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Depending on Driver
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK05
IP (system)	IP40
Outdoor	No
Operating temperature (°C)	-10 - 40

**PRODUCT DATA SHEET**

Panel 595x595 5000lm 930 36W Prism BK EPN0024 w/o driver

Art.no: 0388-02-2

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	126
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000
Color Code	930
Lightsource Type	LED (built in)
Lens (Diffuser)	Micropris.
Lifetime (h)	L80B50: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Runlite

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	900 - null
CC (forward voltage driver) (V)	25.0 - 45.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	5.0
Max load pr circuit - B10	14
Max load pr circuit - B16	24
Max load pr circuit - C10	24
Max load pr circuit - C16	40
Inrush current time (μ s)	150.0
Inrush current I _{max} (A)	25.0

DIMENSIONS	
Length (product) (mm)	595.0
Width (product) (mm)	595.0
Height (product) (mm)	9.5
Weight (product) (kg)	2.4

**PRODUCT DATA SHEET**

Panel 595x595 5000lm 930 36W Prism BK EPN0024 w/o driver

Art.no: 0388-02-2

*Lighting Solutions*

MATERIALS AND SURFACES	
Color	Black
Housing Material	Aluminium
Housing Material %	38.2
Diffuser Material	PMMA
Diffuser Material%	46.26
Material 2%	1.7999999999999998
Material 3%	1.17
Material 4%	3.65
Material 5%	4.29
Material 6%	4.63

INSTALLATION AND CONNECTION	
Areas of use	Generally, Hotel, Office, School, Shop
Mounting	Recessed, Ceiling
Connection (system)	EPN0024

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	E
CE mark	Yes
EPD number	NEPD-14297-14692
Energy Efficiency Class	E

ALTERNATIVE DRIVERS	
Current Setting (mA) ?	900