

**PRODUCT DATA SHEET**

Panel 595x595 5000lm 830 36W Opal IP65 WH EPN0024 no driver

Art.no: 0395-01-3

*Lighting Solutions*

Panel 595x595 5000lm 830 36W Opal IP65 WH EPN0024 no driver



IP65 Panel suitable for interior use. It's designed and developed to suite several applications, and may be recessed, surface mounted or suspended. The Panel has 3000K an opal diffusor. IP65 protected for the front of the unit. Delivered with out driver.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Depending on Driver
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK07
IP (system)	IP65
Outdoor	No
Operating temperature (°C)	-10 - 40

**PRODUCT DATA SHEET**

Panel 595x595 5000lm 830 36W Opal IP65 WH EPN0024 no driver

Art.no: 0395-01-3

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Lens (Diffuser)	Opal
Lifetime (h)	L80B50: 100 000

DRIVER	
Manufacturer (driver)	No driver
CC (driver) [mA]	null - null
CC (forward voltage driver) (V)	null - null

DIMENSIONS	
Length (product) (mm)	595.0
Width (product) (mm)	595.0
Height (product) (mm)	13.0
Weight (product) (kg)	2.6

MATERIALS AND SURFACES	
Color	White
Housing Material	Aluminium
Housing Material %	38.2
Diffuser Material	PMMA
Diffuser Material%	46.26
Material 2%	1.7999999999999998
Material 3%	1.17
Material 4%	3.65
Material 5%	4.29
Material 6%	4.63

INSTALLATION AND CONNECTION	
Areas of use	Generally, Hotel, Office, School, Shop
Mounting	Recessed, Ceiling

**PRODUCT DATA SHEET**

Panel 595x595 5000lm 830 36W Opal IP65 WH EPN0024 no driver

Art.no: 0395-01-3

*Lighting Solutions***INSTALLATION AND CONNECTION**

Connection (system)	EPN0024
---------------------	---------

ENERGY AND CERTIFICATIONS

CE mark	Yes
EPD number	NEPD-14297-14692
Energy Efficiency Class	A+

ALTERNATIVE DRIVERS

Current Setting (mA) ?	900
------------------------	-----