NORLUX®

Lighting Solutions

Panel 595x595 5400lm 840 36W Opal IP65 WH EPN0024 no driver

CE | 230V 50Hz | IP65 | IK07 | A⁺

IP65 Panel suitable for interior use. It`s designed and developed to suite several applications, and may be recessed, surface mounted or suspended. The Panel has 4000K an opal diffusor. IP65 protected for the front of the unit. Delivered with out driver.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Depending on Driver
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK07
IP (system)	IP65
Outdoor	No
Operating temperature (°C)	-10 - 40

PHOTOMETRIC DATA

CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840
Lightsource Type	LED (built in)
Lens (Diffuser)	Opal
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3

DRIVER

Manufacturer (driver)	No driver
CC (driver) [mA]	null - null
CC (forward voltage driver) (V)	null - null

DIMENSIONS

Length (product) (mm)	595.0
Width (product) (mm)	595.0
Heigth (product) (mm)	13.0
Weight (product) (kg)	2.6

MATERIALS AND SURFACES

Color	White
Housing Material	Aluminium
Housing Material %	38.2
Diffuser Material	PMMA
Diffuser Material%	46.26
Material 2%	1.7999999999999998
Material 3%	1.17
Material 4%	3.65
Material 5%	4.29
Material 6%	4.63

INSTALLATION AND CONNECTION

Areas of use	Generally, Hotel, Office, School, Shop

INSTALLATION AND CONNECTION	
Mounting	Recessed, Ceiling
Connection (system)	EPN0024

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A+

ALTERNATIVE DRIVERS	
Current Setting (mA) ?	900