

**PRODUKTDATABLAD**

Panel 595x595 5400lm 840 36W Opal IP65 WH EPN0024 no driver

Art.no: 0396-01-3

*Lighting Solutions*

Panel 595x595 5400lm 840 36W Opal IP65 WH EPN0024 no driver



IP65 Panel for bruk innendørs. Den er konstruert for montering i systemhimling, nedhengt ved hjelp av et wiresystem eller med en monteringsramme slik at panelet kan monteres på himlingsflater. Panelet har IP65 klassifisering fra undersiden og leveres med opal diffusor i 4000K. Velg mellom on/off driver, phasecut eller DALI2 (CLO, Corridor, Push dim and Ready2mains) driver.

ELEKTRISKE DATA	
Beskyttelsesklasse	2
Dimmefunksjon (system)	Avhengig av driver
Spenning (V)	230V 50Hz
Driftspenning LED (mA)	900
Effekt (system) (W)	36

TEKNISK DATA	
IK (system)	IK07

**PRODUKTDATABLAD**

Panel 595x595 5400lm 840 36W Opal IP65 WH EPN0024 no driver

Art.no: 0396-01-3

*Lighting Solutions*

TEKNISK DATA	
IP (system)	IP65
Produkt Familie	Panel IP65
Utendørs	No
Driftstemperatur (°C)	-10 - 40

LYSTEKNISKE DATA	
Lumen ut (system) (lm)	4872
Kald lumen (t=25) fra chip (lm)	5400
Fargegjengivelse (CRI / Ra) (>=)	80
Fargetemperatur (CCT) (K)	4000
Fargekode	840
Lyskildetype	LED (innebygget)
Linse (Diffusor)	Opal
Strålevinkel (°)	110°
Levetid (t)	L80B10: 100 000
MacAdam (SDCM)	3

DRIVER / BALLAST	
Produsent (driver)	Ingen driver
Konstant strøm (CC driver) (mA)	null - null
Konstant strøm (CC driftspenning driver) (V)	null - null

DIMENSJONER	
Lengde (produkt) (mm)	595.0
Bredde (produkt) (mm)	595.0
Høyde (produkt) (mm)	13.0
Vekt (produkt) (kg)	2.6

MATERIALER OG OVERFLATER	
Farge	Hvit
Kapslingsmateriale	Aluminium
Housing Material %	38.2
Diffusere Materiale	PMMA
Diffusere Materiale %	46.26
Materiale 2	Mechanical installed part Steel

**PRODUKTDATABLAD**

Panel 595x595 5400lm 840 36W Opal IP65 WH EPN0024 no driver

Art.no: 0396-01-3

*Lighting Solutions*

MATERIALER OG OVERFLATER	
Materiale 2%	1.7999999999999998
Materiale 3	LED Emitter Chip Indium Gallium Aluminium Phosphorus LED frame Iron Silver Copper Nickel Silver Epoxy Silver Resin
Materiale 3%	1.17
Materiale 4	Circuit board for LED Silica,vitreous Aluminium oxide Calcium-oxide Magnesium-oxide Copper Zinc(metal) Phenol,4,4'-((1-methylethylidene)bis(2,6-dibromo-,polymer with(chloromethyl)oxirane and 4,4'-((1-methylethylidene)bis(phenol) 2-Propenoic acid,2-methyl-,polymer with butyl 2-propenoate and methyl 2-methyl-2 propenoate Phenol,4,4'-((1-methylethylidene)bis-,polymer with 2-aminoethanol and 2-(chloromethyl)oxirane Barium sulphate Silicon dioxide Polychloro copper phthalocyanine Tin Cu
Materiale 4%	3.65
Materiale 5	Cable with Connectors Copper PVC materials Diocetyl Phthalate Diisodecyl phthalate Calcium zinc stabilizer Resin Polyamide Silver
Materiale 5%	4.29
Materiale 6	Diffuserplate Polycarbonate
Materiale 6%	4.63

**PRODUKTDATABLAD**

Panel 595x595 5400lm 840 36W Opal IP65 WH EPN0024 no driver

Art.no: 0396-01-3

*Lighting Solutions*

MONTERING OG TILKOBLING	
Bruksområde	Generelt, Hotell, Kontor, Skole, Butikk
Montering	Innfelt, Tak
Tilkobling (system)	EPN0024

ENERGI OG GODKJENNING	
CE-merke	Yes
Energy Efficiency Class	A+

ALTERNATIVE DRIVERE	
Current Setting (mA) ?	900
Alternativ 1-10V Driver 1	6651152 - Driver 350-1050mA cc 48V cv 50W DALI/1-10V/Push US/UL