



**PRODUCT DATA SHEET**

Leila C Midi Surface 4750lm 830 70° 31W BK DALI
Art.no: 101365-70-2-ddd



Lighting Solutions



Leila C Midi Surface 4750lm 830 70° 31W BK DALI



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK00
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-25 - 50

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	109
CRI / Ra (>=)	80

**PRODUCT DATA SHEET**

Leila C Midi Surface 4750lm 830 70° 31W BK DALI
Art.no: 101365-70-2-ddd



Lighting Solutions

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic

DRIVER	
Manufacturer (driver)	Osram
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
Dimming Minimum Level (%)	1.0
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - 1050
CC (forward voltage driver) (V)	15.0 - 54.0
Output Current Tolerance (%)	3.0
Current Ripple (%)	2.0
Max load pr circuit - B10	35
Max load pr circuit - B16	55
Max load pr circuit - C10	56
Max load pr circuit - C16	94
Max load pr circuit - C20	117
Max load pr circuit - C25	146
Inrush current time (μ s)	50.0
Inrush current I _{max} (A)	20.0

DIMENSIONS	
Width (product) (mm)	190.0
Height (product) (mm)	150.0
Weight (product) (kg)	1.5

**PRODUCT DATA SHEET**

Leila C Midi Surface 4750lm 830 70° 31W BK DALI
Art.no: 101365-70-2-ddd



Lighting Solutions

MATERIALS AND SURFACES	
Color	Black

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Hotel, Office, Residence
Mounting	Surface, Ceiling
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A

LIGHT DISTRIBUTION