



**PRODUCT DATA SHEET**

Leila C Maxi Surface 7200lm 830 70° 48W BK DALI
 Art.no: 101375-70-2-ddd

*Lighting Solutions*

Leila C Maxi Surface 7200lm 830 70° 48W BK DALI



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK00
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-25 - 50

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	119
CRI / Ra (>=)	80

**PRODUCT DATA SHEET**

Leila C Maxi Surface 7200lm 830 70° 48W BK DALI
Art.no: 101375-70-2-ddd



Lighting Solutions

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 60 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic
Forward Current LED (min-max) (mA)	null - 2100
Forward Voltage LED (max tp=25) (V)	39.3
Driftspenning LED (min tp=65) (V)	30.6

DRIVER	
Manufacturer (driver)	Osram
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	600 - 1400
CC (forward voltage driver) (V)	15.0 - 54.0
Output Current Tolerance (%)	3.0
Current Ripple (%)	2.0
Max load pr circuit - B10	12
Max load pr circuit - B16	20
Max load pr circuit - C10	20
Max load pr circuit - C16	34
Max load pr circuit - C20	42
Max load pr circuit - C25	53
Leakage current (mA)	0.5
Inrush current time (µs)	200.0
Inrush current I _{max} (A)	30.0

DIMENSIONS	
Width (product) (mm)	230.0
Height (product) (mm)	150.0

**PRODUCT DATA SHEET**

Leila C Maxi Surface 7200lm 830 70° 48W BK DALI
Art.no: 101375-70-2-ddd



Lighting Solutions

DIMENSIONS	
Weight (product) (kg)	2.6

MATERIALS AND SURFACES	
Color	Black

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Hotel, Office, Residence
Mounting	Surface, Ceiling
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	D
CE mark	Yes
Energy Efficiency Class	A++ - A

LIGHT DISTRIBUTION