



**PRODUCT DATA SHEET**

Leila C Maxi Surface 7200lm 830 70° 48W WH

Art.no: 101375-70-3

*Lighting Solutions*

## Leila C Maxi Surface 7200lm 830 70° 48W WH



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK00
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-25 - 50

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	119
CRI / Ra (>=)	80

**PRODUCT DATA SHEET**

Leila C Maxi Surface 7200lm 830 70° 48W WH

Art.no: 101375-70-3

*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 60 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic
Forward Current LED (min-max) (mA)	null - 2100
Forward Voltage LED (max tp=25) (V)	39.3
Driftspenning LED (min tp=65) (V)	30.6

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	1200 - null
CC (forward voltage driver) (V)	26.0 - 42.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	25.0
Max load pr circuit - B10	35
Max load pr circuit - B16	65
Max load pr circuit - C10	35
Max load pr circuit - C16	65
Max load pr circuit - C20	75
Inrush current time (µs)	100.0
Inrush current I <sub>max</sub> (A)	10.0

DIMENSIONS	
Width (product) (mm)	230.0
Height (product) (mm)	150.0
Weight (product) (kg)	2.6

**PRODUCT DATA SHEET**

Leila C Maxi Surface 7200lm 830 70° 48W WH

Art.no: 101375-70-3

*Lighting Solutions***MATERIALS AND SURFACES**

Color	White
-------	-------

**INSTALLATION AND CONNECTION**

Areas of use	Cottage, Hotel, Office, Residence
Mounting	Surface, Ceiling
Connection (system)	QuickConnect

**ENERGY AND CERTIFICATIONS**

Energy Class EPREL	D
CE mark	Yes
Energy Efficiency Class	A++ - A

**LIGHT DISTRIBUTION**