




PRODUCT DATA SHEET

Rod Midi T 4100lm 930 60° HC 23W BK 3-circuit
Art.no: 101820-60H-2

NORLUX®

Lighting Solutions



Rod Midi T 4100lm 930 60° HC 23W BK 3-circuit



ELECTRICAL DATA

Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA

IP (system)	IP20
Outdoor	No
Operating temperature (°C)	0 - 35

PHOTOMETRIC DATA

Efficacy (system) (lm/W)	143
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000

**PRODUCT DATA SHEET**

Rod Midi T 4100lm 930 60° HC 23W BK 3-circuit
Art.no: 101820-60H-2



PHOTOMETRIC DATA	
Color Code	930
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	honeycomb
Lifetime (h)	L80B10: 100 000
Manufacturer (light source)	Bridgelux

DRIVER	
Flicker-free	Yes

DIMENSIONS	
Length (product) (mm)	162.0
Height (product) (mm)	178.0
Weight (product) (kg)	0.626
Diameter (product) (mm)	86.0

MATERIALS AND SURFACES	
Color	Black
RAL Code	RAL9005
Housing Material	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	E
CE mark	Yes
Energy Efficiency Class	A++ - A