


**PRODUCT DATA SHEET**

Tania Mini Slim 850lm 927 36° 9W 1-cir Brushed Brass phase

Art.no: 101910-36-21-p

*Lighting Solutions*

## Tania Mini Slim 850lm 927 36° 9W 1-cir Brushed Brass phase



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	83
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	2700
Color Code	927

**PRODUCT DATA SHEET**

Tania Mini Slim 850lm 927 36° 9W 1-cir Brushed Brass phase

Art.no: 101910-36-21-p

*Lighting Solutions*

PHOTOMETRIC DATA	
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
Manufacturer (light source)	Bridgelux
Forward Voltage LED (max tp=25) (V)	38.1
Driftspenning LED (min tp=65) (V)	32.3

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	48
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Trailing edge
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (forward voltage driver) (V)	20.0 - 40.0
Current Ripple (%)	20.0
Max load pr circuit - B16	125
Max load pr circuit - C10	200
Max load pr circuit - C16	125
Max load pr circuit - C20	200
Inrush current time ( $\mu$ s)	100.0
Inrush current I <sub>max</sub> (A)	5.0

DIMENSIONS	
Heighth (product) (mm)	142.0
Weight (product) (kg)	0.3
Diameter (product) (mm)	42.0

**PRODUCT DATA SHEET**

Tania Mini Slim 850lm 927 36° 9W 1-cir Brushed Brass phase

Art.no: 101910-36-21-p

*Lighting Solutions*

MATERIALS AND SURFACES	
Color	Brushed Brass
Housing Material	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Cafe, Cottage, Generally, Hotel, Residence, Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 1-Circuit

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes
Energy Efficiency Class	A++ - A