



PRODUCT DATA SHEET

Joule 7000lm 940 50W P3 Assymmetric IP66 GR DALI 5m cable Ø60
Art.no: 102018-03-2-ddd



Lighting Solutions



Joule 7000lm 940 50W P3 Assymmetric IP66 GR DALI 5m cable Ø60



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI2
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK09
IP (system)	IP66
Outdoor	Yes
Operating temperature (°C)	-30 - 50
Wind force (EPA) (m ²) at 0°	0.15

**PRODUCT DATA SHEET**

Joule 7000lm 940 50W P3 Assymetric IP66 GR DALI 5m cable Ø60
Art.no: 102018-03-2-ddd



Lighting Solutions

PHOTOMETRIC DATA	
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	4000
Color Code	940
Lightsource Type	LED (built in)
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	5
Manufacturer (light source)	MTC OPTOELECTRONICS

DRIVER	
Surge Protection	L/N-PE = 10KV, L-N = 5KV
Max load pr circuit - B10	31
Max load pr circuit - B16	50
Max load pr circuit - C10	31
Max load pr circuit - C16	50
Max load pr circuit - C20	63
Max load pr circuit - C25	79
Max load pr circuit - C32	101

DIMENSIONS	
Length (product) (mm)	615.0
Width (product) (mm)	350.0
Height (product) (mm)	225.0

MATERIALS AND SURFACES	
Color	Grey
RAL Code	RAL7022
Corrosion Class	C4
Housing Material	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Outdoor, Parking, Street
Mounting	Wall, Mast
Connection (system)	Cable 5m



PRODUCT DATA SHEET

Joule 7000lm 940 50W P3 Assymetric IP66 GR DALI 5m cable Ø60

Art.no: 102018-03-2-ddd



Lighting Solutions

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	C
CE mark	Yes