


**PRODUCT DATA SHEET**

Cylinder 60 G2 1400lm 930 36° (15°&amp;24°) 15W WH 3-cir phasec

Art.no: 102261-36-3-p

*Lighting Solutions*

## Cylinder 60 G2 1400lm 930 36° (15°&24°) 15W WH 3-cir phasec



Cylinder 60 G2 is an elegant and modern spotlight, designed to deliver high light output and exceptional color rendering in various environments. With a diameter of 60mm and length of 130mm, this spotlight is both discreet and efficient. Available with beam angles of 15°, 24°, or 36° and color temperatures of 2700K, 3000K, or Dim 2 Warm (3000-1800K). CRI90 ensures excellent color rendering. Equipped with phase-cut dimming. Made of powder-coated aluminum, Cylinder 60 G2 is ideal for use in bedrooms, cafes, cabins, hotels, kitchens, and homes. The built-in driver in the sleek fixture housing provides a clean and modern appearance, while the spotlight can be tilted up to 90° and rotated 350° around its own axis for optimal adjustability. This makes Cylinder 60 perfect for both private and commercial environments.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz
Power (system) (W)	15
Lightsource Max. Power (W) if Socket	na
Emergency light (h)	No Emergency light

**PRODUCT DATA SHEET**

Cylinder 60 G2 1400lm 930 36° (15°&24°) 15W WH 3-cir phasec  
Art.no: 102261-36-3-p



*Lighting Solutions*

TECHNICAL DATA	
IK (system)	IK02
IP (system)	IP20
IP Front/Back (system)	IP20/20
Product Family	Cylinder 60
Outdoor	No
Operating temperature (°C)	-20 - 45

PHOTOMETRIC DATA	
Lumen Out (system) (lm)	1420
Efficacy (system) (lm/W)	100
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000
Color Code	930
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80: 100 000
MacAdam (SDCM)	3
UGR (<=)	19
Manufacturer (light source)	Bridgelux
Forward Current LED (min-max) (mA)	100 - 540
Forward Voltage LED (max tp=25) (V)	36.2
Driftspenning LED (min tp=65) (V)	32.0

DRIVER	
Manufacturer (driver)	KGP
Protection Class (driver)	2
Standby power P <sub>sb</sub> (W) <	0.5
Flicker metric (P <sub>st</sub> LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	39
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	10.0
Dimming Phasecut Type	Leading / Trailing edge

**PRODUCT DATA SHEET**

Cylinder 60 G2 1400lm 930 36° (15°&amp;24°) 15W WH 3-cir phasec

Art.no: 102261-36-3-p

*Lighting Solutions*

DRIVER	
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	332 - 367
CC (forward voltage driver) (V)	27.0 - 39.0
CV (driver) [V]	36
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	50
Max load pr circuit - B16	80
Max load pr circuit - C10	80
Max load pr circuit - C16	128
Max load pr circuit - C20	160
Max load pr circuit - C25	200
Max load pr circuit - C32	256
Leakage current (mA)	0.25
Inrush current time (µs)	400.0
Inrush current I <sub>max</sub> (A)	12.0

DIMENSIONS	
Length (product) (mm)	130.0
Height (product) (mm)	130.0
Weight (product) (kg)	0.525
Diameter (product) (mm)	60.0

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9010
Corrosion Class	C1
Surface treatment	Powdercoated
Housing Material	Aluminium
Diffuser Material	Aluminium

**PRODUCT DATA SHEET**

Cylinder 60 G2 1400lm 930 36° (15°&amp;24°) 15W WH 3-cir phasec

Art.no: 102261-36-3-p

*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Bedroom, Cafe, Cottage, Hotel, Kitchen, Office, Residence, Restaurant, Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	E
CE mark	Yes
Energy Efficiency Class	E

**LIGHT DISTRIBUTION**