

**PRODUCT DATA SHEET**

Cylinder 60 G2 1400lm 940 36° (15°&24°) 15W WH 3-cir DALI

Art.no: 102262-36-3-ddd

*Lighting Solutions*

Cylinder 60 G2 1400lm 940 36° (15°&24°) 15W WH 3-cir DALI



Cylinder 60 G2 is an elegant and modern spotlight, designed to deliver high light output and exceptional color rendering in various environments. With a diameter of 60mm and length of 130mm, this spotlight is both discreet and efficient. Available with beam angles of 15°, 24°, or 36° and color temperatures of 2700K, 3000K, or Dim 2 Warm (3000-1800K). CRI90 ensures excellent color rendering. Equipped with phase-cut dimming. Made of powder-coated aluminum, Cylinder 60 G2 is ideal for use in bedrooms, cafes, cabins, hotels, kitchens, and homes. The built-in driver in the sleek fixture housing provides a clean and modern appearance, while the spotlight can be tilted up to 90° and rotated 350° around its own axis for optimal adjustability. This makes Cylinder 60 perfect for both private and commercial environments.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	DALI2
Voltage (system) [V]	230V 50Hz
Lightsource Max. Power (W) if Socket	na
Emergency light (h)	No Emergency light

**PRODUCT DATA SHEET**

Cylinder 60 G2 1400lm 940 36° (15°&24°) 15W WH 3-cir DALI

Art.no: 102262-36-3-ddd

*Lighting Solutions*

TECHNICAL DATA	
IK (system)	IK02
IP (system)	IP20
IP Front/Back (system)	IP20/20
Product Family	Cylinder 60
Outdoor	No
Operating temperature (°C)	-20 - 45

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	100
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	4000
Color Code	940
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 50.000

DRIVER	
Flicker-free	Yes

DIMENSIONS	
Length (product) (mm)	130.0
Weight (product) (kg)	0.45
Diameter (product) (mm)	60.0

MATERIALS AND SURFACES	
Surface treatment	Powdercoated
Housing Material	Aluminium
Diffuser Material	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Bedroom, Cafe, Cottage, Hotel, Kitchen, Office, Residence, Restaurant, Shop, Showroom
Mounting	Track, Ceiling



PRODUCT DATA SHEET

Cylinder 60 G2 1400lm 940 36° (15°&24°) 15W WH 3-cir DALI

Art.no: 102262-36-3-ddd



Lighting Solutions

ENERGY AND CERTIFICATIONS

CE mark	Yes
---------	-----