

**PRODUCT DATA SHEET**

Universal G2 3200lm 830/840 105° 20/16/13/11W 600mm WH MW

Art.no: 102471-MW-105-3

*Lighting Solutions*

Universal G2 3200lm 830/840 105° 20/16/13/11W 600mm WH MW



Universal is an elegant and splash-proof IP44 LED luminaire designed for interior and industrial use. It features easy installation with pass-through wiring, low glare, and up to 150lm/W efficiency. The luminaire comes with a DIP switch, allowing you to customize the power level as needed, and the Kelvin can be adjusted between 3000K and 4000K. Available in lengths of 600mm, 1200mm, and 1500mm in on/off, sensor (Microwave), or DALI version. This product is also available with a microwave sensor with wireless communication between luminaires, using the Norlux Wireless Connect system for control.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK07
IP (system)	IP44

**PRODUCT DATA SHEET**

Universal G2 3200lm 830/840 105° 20/16/13/11W 600mm WH MW

Art.no: 102471-MW-105-3

*Lighting Solutions*

TECHNICAL DATA	
Outdoor	No
Operating temperature (°C)	-20 - 40
Through-wiring (mm ²)	5x2,5

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000-4000K
Color Code	830/840
Lightsource Type	LED (replaceable)
Socket / Cap-Base	N/A
Lens (Diffuser)	Micropris.
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
UGR (<=)	22
Manufacturer (light source)	Shenzhen leadopto Technology Co.Ltd
Forward Current LED (min-max) (mA)	0 - 150

DRIVER	
Manufacturer (driver)	Lifud
Protection Class (driver)	1
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	57
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	200 - 350
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	30
Max load pr circuit - B16	48
Max load pr circuit - C10	49
Max load pr circuit - C16	81

**PRODUCT DATA SHEET**

Universal G2 3200lm 830/840 105° 20/16/13/11W 600mm WH MW

Art.no: 102471-MW-105-3

*Lighting Solutions*

DRIVER	
Max load pr circuit - C20	99
Max load pr circuit - C25	124
Max load pr circuit - C32	174
Leakage current (mA)	0.7
Inrush current time (µs)	150.0
Inrush current I _{max} (A)	19.0

DIMENSIONS	
Length (product) (mm)	600.0
Width (product) (mm)	156.0
Height (product) (mm)	52.0
Weight (product) (kg)	1.43

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9003
Housing Material	Steel
Diffuser Material	PMMA

INSTALLATION AND CONNECTION	
Areas of use	Generally, Industrial
Mounting	Surface, Ceiling
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	C
CE mark	Yes
D-mark	Yes
EPD number	NEPD-11302-11245