

**PRODUCT DATA SHEET**

Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø160-170mm
Art.no: 102620-S-60-3



Lighting Solutions



Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø160-170mm



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Sensor (PIR)
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP44
Outdoor	No
Operating temperature (°C)	-20 - 40

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	138

**PRODUCT DATA SHEET**

Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø160-170mm
Art.no: 102620-S-60-3



Lighting Solutions

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3/4/5700
Preset CCT if switch(Color Temperature) (K)	3000
Color Code	830/840/857
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lifetime (h)	L80B10: 100 000
UGR (<=)	19

DRIVER	
Leakage current (mA)	0.16

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9016

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Generally, Hotel, Office, Residence, School, Shop
Mounting	Recessed, Ceiling
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
CE mark	Yes

ALTERNATIVE DRIVERS	
Current Setting (mA) ?	320