

**PRODUCT DATA SHEET**

Tania Slim Bed G2 500lm 927 34° 4,5W w/switch BK
Art.no: 102660-2-36-2



Lighting Solutions



Tania Slim Bed G2 500lm 927 34° 4,5W w/switch BK



Tania Slim Bed is an elegant and functional lamp, perfect for mounting above the bedside table in the bedroom, whether at home, in a cabin, or a hotel room. The adjustable lamp head allows you to rotate the light to suit your needs. The lamp is classified as IP20 and protection class 1 for safe use.

Available in three stylish finishes – black, brushed brass, and brushed titanium – Tania Slim Bed fits seamlessly into any interior.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz
Lightsource Max. Power (W) if Socket	5.87

TECHNICAL DATA	
IK (system)	IK01
IP (system)	IP20

**PRODUCT DATA SHEET**

Tania Slim Bed G2 500lm 927 34° 4,5W w/switch BK

Art.no: 102660-2-36-2

*Lighting Solutions*

TECHNICAL DATA	
Outdoor	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	76
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	2700
Color Code	927
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	2
UGR (<=)	15
Manufacturer (light source)	Bridgelux

DRIVER	
Manufacturer (driver)	KGP
Protection Class (driver)	2
Standby power P _{sb} (W) <	0.5
Flicker metric (P _{st} LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	13
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	500 - null
Output Current Tolerance (%)	5.0
Max load pr circuit - B10	40
Max load pr circuit - B16	64
Max load pr circuit - C10	64
Max load pr circuit - C16	102
Max load pr circuit - C20	128
Max load pr circuit - C25	160

**PRODUCT DATA SHEET**

Tania Slim Bed G2 500lm 927 34° 4,5W w/switch BK

Art.no: 102660-2-36-2

*Lighting Solutions*

DIMENSIONS	
Length (product) (mm)	188.0
Width (product) (mm)	100.0
Height (product) (mm)	100.0
Weight (product) (kg)	0.48
Diameter (product) (mm)	42.0

MATERIALS AND SURFACES	
Color	Black
RAL Code	RAL9006
Corrosion Class	C2

INSTALLATION AND CONNECTION	
Areas of use	Inndoor, Bedroom, Cottage, Hotel, Residence
Mounting	Surface, Wall
Connection (system)	Terminal

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes