


**PRODUCT DATA SHEET**

Cilla Mini 670lm 7W 927 30° BK/BK IP44 Ø68mm w/o Driver
 Art.no: 102720-30-2

*Lighting Solutions*

Cilla Mini 670lm 7W 927 30° BK/BK IP44 Ø68mm w/o Driver



Cilla Mini is an elegant and functional downlight, perfect for hotels, restaurants, or modern homes. It provides comfortable and atmospheric lighting with low glare, thanks to its high color rendering index of CRI 95 and a warm color temperature of 2700K or 3000K. With a recessed light source, it creates an inviting ambiance that highlights details.

With a compact design measuring 80mm in diameter and 76.5mm in height, Cilla Mini integrates seamlessly into any room. Its IP44 rating ensures that the lamp is both dust and splash-resistant, making it ideal for various applications. Designed for recessed installation, it is supplied without a driver, which must be purchased separately. For added flexibility, you can choose between front rings in three different colors to match your interior style.

Cilla Mini – the perfect combination of design, functionality, and quality.

ELECTRICAL DATA	
Protection Class (system)	3
Dimming (system)	Depending on Driver
Voltage (system) [V]	230V 50Hz
Lightsource Max. Power (W) if Socket	/
Emergency light (h)	No Emergency light

**PRODUCT DATA SHEET**

Cilla Mini 670lm 7W 927 30° BK/BK IP44 Ø68mm w/o Driver

Art.no: 102720-30-2

*Lighting Solutions*

TECHNICAL DATA	
IK (system)	IK02
IP (system)	IP44
IP Front/Back (system)	IP40/20
Outdoor	No
Operating temperature (°C)	-20 - 45

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	95
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	2700
Color Code	927
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Lens
Lifetime (h)	L80: 100 000
MacAdam (SDCM)	3
UGR (<=)	19
Manufacturer (light source)	Bridgelux
Forward Current LED (min-max) (mA)	100 - 540
Forward Voltage LED (max tp=25) (V)	38.0
Driftspenning LED (min tp=65) (V)	33.0

DRIVER	
Flicker-free	Yes
CC (driver) [mA]	null - null
CC (forward voltage driver) (V)	null - null

DIMENSIONS	
Length (product) (mm)	80.0
Width (product) (mm)	80.0
Height (product) (mm)	76.5
Weight (product) (kg)	0.2361111111111111
Diameter (product) (mm)	80.0

**PRODUCT DATA SHEET**

Cilla Mini 670lm 7W 927 30° BK/BK IP44 Ø68mm w/o Driver

Art.no: 102720-30-2

*Lighting Solutions*

MATERIALS AND SURFACES	
Color	Black
RAL Code	RAL9005
Corrosion Class	C1
Surface treatment	Powdercoated
Housing Material	Aluminium
Housing Material %	49.0
Diffuser Material	Aluminium
Diffuser Material%	0.5599999999999999
Recycled Plastic %	37.35
Recycled Aluminium %	41.25
Material 2%	1.0
Material 3%	2.16
Material 4%	3.34
Material 5%	0.11
Material 6%	0.36
Material 7%	6.49
Material 8%	5.09
Material 9%	6.22

INSTALLATION AND CONNECTION	
Areas of use	Hotel
Mounting	Recessed
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	E
CE mark	Yes
EPD number	NEPD-14363-14755