

**PRODUCT DATA SHEET**

Ufo T 13000lm 927 120° 100/80/60W BK 1-10V 1m 18i3

Art.no: 102762-02-2

*Lighting Solutions*

## Ufo T 13000lm 927 120° 100/80/60W BK 1-10V 1m 18i3



The Ufo T High Bay is ideal for commercial areas such as warehouses, workshops, and industrial halls. This LED fixture comes with a power switch, allowing you to easily set the desired output.

The Ufo T High Bay is both durable and energy-efficient. It has an IP65 rating for good protection against dust and water splashes. The fixture is available in various sizes and has a robust construction with an IK08 safety rating.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	0-10V
Voltage (system) [V]	230V 50Hz
Emergency light (h)	No Emergency light
Emergency light testing	N/A

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP65

**PRODUCT DATA SHEET**

Ufo T 13000lm 927 120° 100/80/60W BK 1-10V 1m 18i3

Art.no: 102762-02-2

*Lighting Solutions*

TECHNICAL DATA	
Outdoor	No
Operating temperature (°C)	-30 - 50

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	121
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	2700
Color Code	927
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
UGR (<=)	26
Manufacturer (light source)	Lumileds
Forward Current LED (min-max) (mA)	30 - 150
Forward Voltage LED (max tp=25) (V)	3.0
Driftspenning LED (min tp=65) (V)	2.9

DRIVER	
Manufacturer (driver)	Lifud
Protection Class (driver)	1
Standby power P <sub>sb</sub> (W) <	0.5
Flicker metric (P <sub>st</sub> LM) <	0.1
Stroboscopic effect metric (SVM) <	1.0
Max Output Voltage (V)	260
Dimming (driver)	PWM, 0-10V, RX
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
Dimming output type	PWM
IP (driver)	IP65
Expected Lifetime (driver) (h)	50000
Flicker-free	No
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	300 - 500
Output Current Tolerance (%)	5.0

**PRODUCT DATA SHEET**

Ufo T 13000lm 927 120° 100/80/60W BK 1-10V 1m 18i3

Art.no: 102762-02-2

*Lighting Solutions*

DRIVER	
Max load pr circuit - B10	11
Max load pr circuit - B16	18
Max load pr circuit - C10	12
Max load pr circuit - C16	18
Max load pr circuit - C20	23
Max load pr circuit - C25	29
Max load pr circuit - C32	36
Leakage current (mA)	5.0
Inrush current time (µs)	350.0
Inrush current I <sub>max</sub> (A)	80.0

CONTROL SYSTEM	
Norlux Wireless Connect	Compatible

DIMENSIONS	
Length (product) (mm)	240.0
Width (product) (mm)	240.0
Height (product) (mm)	166.0
Weight (product) (kg)	1.5
Diameter (product) (mm)	240.0

MATERIALS AND SURFACES	
Color	Black
RAL Code	RAL9004
Corrosion Class	C3
Housing Material	Aluminium
Housing Material %	69.0
Diffuser Material	Polycarbonate
Diffuser Material%	3.0
Recycled Aluminium %	95.0
Material 2%	0.8999999999999999
Material 3%	0.3
Material 4%	6.5
Material 5%	10.0
Material 6%	5.4

**PRODUCT DATA SHEET**

Ufo T 13000lm 927 120° 100/80/60W BK 1-10V 1m 18i3

Art.no: 102762-02-2

*Lighting Solutions***MATERIALS AND SURFACES**

Material 7%	4.9
-------------	-----

**INSTALLATION AND CONNECTION**

Areas of use	Industrial
Mounting	Suspended, Wall, Ceiling
Connection (system)	18i3 5m + 2x0,4m free end

**ENERGY AND CERTIFICATIONS**

Energy Class EPREL	C
CE mark	Yes
EPD number	NEPD-12961-14216