



FDV SPEC SHEET

Blume

Art. no: 102780-38-2



Blume



Art. no: 102780-38-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2400
Lumen LED (tc=25):	2760
Beam Angle:	38
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Lens
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	EPN0024
Cut-out [mm]:	200-220
Mounting:	Recessed, Ceiling

ELECTRICAL DATA

Dimming:	Depending on Driver
Flickerfree:	Yes
System Power [W]:	25
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	540
Voltage Forward Min [V]:	33
Voltage Forward Max [V]:	38
Emergency light [h]:	No Emergency light
Emergency light testing:	N/A



FDV SPEC SHEET

Blume

Art. no: 102780-38-2



PRODUCT	
Ingress Protection:	IP65
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9005
Length [mm]:	235
Height [mm]:	81
Width [mm]:	235
Diameter [mm]:	235
Weight [kg]:	1,27
Housing Material :	Aluminium
Diffuser Material:	Polycarbonate
Material 2:	Polycarbonate