

**PRODUCT DATA SHEET**

Iota Marine 45000lm 740 Asymmetric 300/225/150W BK IP66

Art.no: 102842-02-2

*Lighting Solutions*

Iota Marine 45000lm 740 Asymmetric 300/225/150W BK IP66



Iota Marine is ideal for outdoor use and sports facilities that require durable lighting capable of withstanding challenging weather conditions. This LED light has a C5 corrosion class and IP66 rating, providing extra protection against water and dust. Additionally, Iota Marine offers a lifespan of up to 100,000 hours (L80B10) and delivers flicker-free illumination

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP66
Outdoor	Yes
Operating temperature (°C)	-30 - 50

**PRODUCT DATA SHEET**

Iota Marine 45000lm 740 Asymmetric 300/225/150W BK IP66

Art.no: 102842-02-2

*Lighting Solutions*

TECHNICAL DATA	
Wind force (EPA) (m ²) at 0°	0.17

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	143
CRI / Ra (>=)	70
CCT (Color Temperature) (K)	4000
Color Code	740
Lightsource Type	LED (replaceable)
Socket / Cap-Base	N/A
Lens (Diffuser)	Lens
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	5
Manufacturer (light source)	MTC OPTOELECTRONICS
Forward Current LED (min-max) (mA)	20 - 150
Forward Voltage LED (max tp=25) (V)	6.2
Driftspenning LED (min tp=65) (V)	5.6

DRIVER	
Manufacturer (driver)	Done
Protection Class (driver)	1
Standby power Psb (W) <	0.5
Flicker metric (Pst LM) <	0.014
Stroboscopic effect metric (SVM) <	0.023
Max Output Voltage (V)	56
Dimming (driver)	0-10V
Dimming Minimum Level (%)	7.0
Dimming output type	Amplitude Modulation
IP (driver)	IP67
Expected Lifetime (driver) (h)	80000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	4200 - 7650
Current setting (driver)	None
CC (forward voltage driver) (V)	25.0 - 56.0
CV (driver) [V]	47

**PRODUCT DATA SHEET**

Iota Marine 45000lm 740 Asymmetric 300/225/150W BK IP66

Art.no: 102842-02-2

*Lighting Solutions*

DRIVER	
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	4
Max load pr circuit - B16	6
Max load pr circuit - C10	5
Max load pr circuit - C16	8
Max load pr circuit - C20	10
Leakage current (mA)	0.7
Inrush current time (μ s)	364.0
Inrush current I _{max} (A)	81.0

DIMENSIONS	
Length (product) (mm)	495.0
Width (product) (mm)	75.0
Height (product) (mm)	419.0
Weight (product) (kg)	6.4

MATERIALS AND SURFACES	
Color	Black
RAL Code	RAL9017
Corrosion Class	C5

INSTALLATION AND CONNECTION	
Areas of use	Outdoor, Sports areas
Mounting	Wall
Connection (system)	Cable 1.5m

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	D
CE mark	Yes