

**PRODUCT DATA SHEET**

Mika29 Bollard 1100lm 840 12W IP65 IK08 Antracite
Art.no: 102920-5



Lighting Solutions



Mika29 Bollard 1100lm 840 12W IP65 IK08 Antracite



The Mika29 Bollard is ideal for outdoor areas such as parks and walkways, providing stylish and modern lighting to its surroundings. With its anthracite grey finish (RAL7016), it offers an elegant look that suits a variety of environments. Its high protection rating of IP65 ensures resistance to both dust and water, making the Mika29 perfectly suited for outdoor use.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP65
Outdoor	Yes
Operating temperature (°C)	-25 - 45

**PRODUCT DATA SHEET**

Mika29 Bollard 1100lm 840 12W IP65 IK08 Antracite

Art.no: 102920-5

*Lighting Solutions*

TECHNICAL DATA	
Wind force (EPA) (m ²) at 0°	0.126

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	87
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840
Lightsource Type	LED (replaceable)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	6
Manufacturer (light source)	Philips
Forward Voltage LED (max tp=25) (V)	6.6
Driftspenning LED (min tp=65) (V)	5.8

DRIVER	
Manufacturer (driver)	Eaglerise
Protection Class (driver)	2
Standby power P _{sb} (W) <	0.5
Flicker metric (P _{st} LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	35
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	30000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - null
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	53
Max load pr circuit - B16	77
Max load pr circuit - C10	66
Max load pr circuit - C16	96

**PRODUCT DATA SHEET**

Mika29 Bollard 1100lm 840 12W IP65 IK08 Antracite

Art.no: 102920-5

*Lighting Solutions*

DRIVER	
Max load pr circuit - C20	100
Max load pr circuit - C25	104
Max load pr circuit - C32	108
Leakage current (mA)	0.7
Inrush current time (μ s)	400.0
Inrush current I _{max} (A)	30.0

DIMENSIONS	
Width (product) (mm)	170.0
Height (product) (mm)	1000.0
Weight (product) (kg)	4.0
Diameter (product) (mm)	217.0

MATERIALS AND SURFACES	
Color	Antracite
RAL Code	RAL7016
Corrosion Class	C4
Surface treatment	Powdercoated
Housing Material	Aluminium
Housing Material %	75.0
Diffuser Material	Polycarbonate
Diffuser Material%	6.0
Recycled Plastic %	0.0
Recycled Aluminium %	97.0
Material 2%	8.0
Material 3%	0.44999999999999996
Material 4%	0.49
Material 5%	0.54
Material 6%	5.8999999999999995
Material 7%	2.5
Material 8%	1.0
Material 9%	0.12

INSTALLATION AND CONNECTION	
Areas of use	Outdoor, Park



PRODUCT DATA SHEET

Mika29 Bollard 1100lm 840 12W IP65 IK08 Antracite

Art.no: 102920-5



Lighting Solutions

INSTALLATION AND CONNECTION	
Mounting	Bollard
Connection (system)	Cable 1.5m

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	D
CE mark	Yes
EPD number	NEPD-12546-12575

LIGHT DISTRIBUTION

