



## Ledstripekampanje Phasecut 5



| ELECTRICAL DATA           |                     |
|---------------------------|---------------------|
| Protection Class (system) | 3                   |
| Dimming (system)          | Depending on Driver |
| Voltage (system) [V]      | 24VDC               |
| Power pr. meter (W/m)     | 14.4                |

| TECHNICAL DATA             |          |
|----------------------------|----------|
| IP (system)                | IP20     |
| Outdoor                    | No       |
| Operating temperature (°C) | -20 - 50 |
| Heat sink needed           | No       |

| PHOTOMETRIC DATA         |    |
|--------------------------|----|
| Efficacy (system) (lm/W) | 77 |



| PHOTOMETRIC DATA            |      |
|-----------------------------|------|
| CRI / Ra (>=)               | 90   |
| CCT (Color Temperature) (K) | 2700 |
| Color Code                  | 927  |
| MacAdam (SDCM)              | 3    |
| LED Chip                    | 2835 |
| LED/m                       | 120  |
| Lumen pr. meter (lm/m)      | 1100 |

| DRIVER                                 |    |
|--|----|
| Constant current or voltage (CC or CV) | CV |

| DIMENSIONS            |        |
|-----------------------|--------|
| Length (product) (mm) | 5000.0 |
| Width (product) (mm)  | 10.0   |
| Weight (product) (kg) | 0.15   |
| Max. length (m)       | 5      |

| INSTALLATION AND CONNECTION |               |
|-----------------------------|---------------|
| LED Strip Mounting          | Adhesive tape |
| Connection LED Strip        | Cable 2m      |

| ENERGY AND CERTIFICATIONS |     |
|---------------------------|-----|
| CE mark                   | Yes |