


**PRODUCT DATA SHEET**

Mika29 Pole 4500lm 840 33W IP65 IK08 Antracite 6m Cable Asym

Art.no: 102945-5

*Lighting Solutions*

Mika29 Pole 4500lm 840 33W IP65 IK08 Antracite 6m Cable Asym



The Mika29 Pole is ideal for illuminating outdoor areas such as gardens, driveways, and parking lots. It creates an inviting atmosphere while providing excellent visibility and enhanced safety. With an anthracite grey color (RAL7016) and an IP65 protection rating, it is well-protected against dust and water. Additionally, the product has an IK08 impact resistance, making it extra durable and perfect for outdoor use.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP65
Outdoor	Yes

**PRODUCT DATA SHEET**

Mika29 Pole 4500lm 840 33W IP65 IK08 Antracite 6m Cable Asym
Art.no: 102945-5



Lighting Solutions

TECHNICAL DATA	
Operating temperature (°C)	-25 - 45
Wind force (EPA) (m ²) at 0°	0.146

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	137
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Lens
Lifetime (h)	L80B20: 100 000
MacAdam (SDCM)	3

DRIVER	
Manufacturer (driver)	Sosen
Max load pr circuit - B10	6
Max load pr circuit - B16	10
Max load pr circuit - C10	11
Max load pr circuit - C16	18
Max load pr circuit - C20	22
Max load pr circuit - C25	28
Max load pr circuit - C32	36
Leakage current (mA)	0.7
Inrush current I _{max} (A)	40.0

DIMENSIONS	
Height (product) (mm)	635.0
Diameter (product) (mm)	500.0

MATERIALS AND SURFACES	
Color	Antracite
RAL Code	RAL7016
Corrosion Class	C4



PRODUCT DATA SHEET

Mika29 Pole 4500lm 840 33W IP65 IK08 Antracite 6m Cable Asym
Art.no: 102945-5



Lighting Solutions

INSTALLATION AND CONNECTION	
Areas of use	Outdoor, Park, Parking
Mounting	Mast
Connection (system)	Cable 6m

ENERGY AND CERTIFICATIONS	
CE mark	Yes
EPD number	NEPD-12511-12618

LIGHT DISTRIBUTION

