

**PRODUCT DATA SHEET**

T-Line Louvre Wing 11200lm 930 60° 70-40W 1500mm WH

Art.no: 103130-60-3

*Lighting Solutions*

T-Line Louvre Wing 11200lm 930 60° 70-40W 1500mm WH



T-Line Louvre is the latest addition to our T-Line family, designed with a focus on maximum light output and minimal glare. This revolutionary lighting solution provides strong, clear illumination that is comfortable for the eyes, making it ideal for both professional and residential environments.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK03
IP (system)	IP40
Outdoor	No
Operating temperature (°C)	-25 - 60

**PRODUCT DATA SHEET**

T-Line Louvre Wing 11200lm 930 60° 70-40W 1500mm WH

Art.no: 103130-60-3

*Lighting Solutions*

PHOTOMETRIC DATA	
Lumen Out (system) (lm)	10550
Lumen Out per Watt with Dip Switch	148
Efficacy (system) (lm/W)	150
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000
Color Code	930
Lightsource Type	LED (built in)
Lens (Diffuser)	Lens
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
UGR (<=)	19
Manufacturer (light source)	Bridgelux
Forward Current LED (min-max) (mA)	200 - 550

DRIVER	
Manufacturer (driver)	Boke
Protection Class (driver)	1
Flicker metric (Pst LM) <	0.016
Stroboscopic effect metric (SVM) <	0.041
Max Output Voltage (V)	216
Dimming (driver)	None
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	200 - 550
CC (forward voltage driver) (V)	50.0 - 216.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	3.0
Max load pr circuit - B10	13
Max load pr circuit - B16	21
Max load pr circuit - C10	21
Max load pr circuit - C16	34
Max load pr circuit - C20	42
Max load pr circuit - C25	52

**PRODUCT DATA SHEET**

T-Line Louvre Wing 11200lm 930 60° 70-40W 1500mm WH

Art.no: 103130-60-3

*Lighting Solutions*

DRIVER	
Max load pr circuit - C32	68
Leakage current (mA)	0.54
Inrush current time (µs)	254.0
Inrush current I _{max} (A)	20.94

DIMENSIONS	
Length (product) (mm)	1665.0
Width (product) (mm)	62.0
Height (product) (mm)	44.0
Weight (product) (kg)	2.3

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9016
Surface treatment	Galvanized
Housing Material	Aluminium
Housing Material %	45.0
Diffuser Material	PMMA
Diffuser Material%	30.0

INSTALLATION AND CONNECTION	
Areas of use	Generally, Shop
Mounting	Suspended
Connection (system)	18i3 Quick connection

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	C
CE mark	Yes



PRODUCT DATA SHEET

T-Line Louvre Wing 11200lm 930 60° 70-40W 1500mm WH

Art.no: 103130-60-3



Lighting Solutions

LIGHT DISTRIBUTION

