


**PRODUCT DATA SHEET**

NDL190-A 3800lm 840 60° 25W WH Ø160-175 w/o driver

Art.no: 103270-60-3

*Lighting Solutions*

NDL190-A 3800lm 840 60° 25W WH Ø160-175 w/o driver



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Depending on Driver
Voltage (system) [V]	230V 50Hz
Emergency light (h)	No Emergency light
Emergency light testing	N/A

TECHNICAL DATA	
IK (system)	IK03
IP (system)	IP54
IP Front/Back (system)	IP54/20
Outdoor	No
Operating temperature (°C)	-20 - 45

**PRODUCT DATA SHEET**

NDL190-A 3800lm 840 60° 25W WH Ø160-175 w/o driver

Art.no: 103270-60-3

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	143
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Preset CCT if switch(Color Temperature) (K)	4000
Color Code	840
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Frosted
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
UGR (<=)	19
Manufacturer (light source)	Hong Li Zhi Hui Group Co., Ltd
Forward Current LED (min-max) (mA)	600 - 600
Forward Voltage LED (max tp=25) (V)	40.0
Driftspenning LED (min tp=65) (V)	30.0

DRIVER	
Manufacturer (driver)	No driver
Flicker-free	Yes

DIMENSIONS	
Length (product) (mm)	190.0
Width (product) (mm)	190.0
Height (product) (mm)	99.0
Weight (product) (kg)	0.52
Diameter (product) (mm)	190.0

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9016
Corrosion Class	C1
Housing Material	Aluminium
Diffuser Material	Aluminium

**PRODUCT DATA SHEET**

NDL190-A 3800lm 840 60° 25W WH Ø160-175 w/o driver

Art.no: 103270-60-3

*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Generally
Mounting	Recessed
Connection (system)	EPN0024

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	D
CE mark	Yes