

**PRODUCT DATA SHEET**

Halo Pendant 3200lm 830 120° 28W Gold/White Phasecut Ø80cm

Art.no: 1127-2-120-9

*Lighting Solutions*

Halo Pendant 3200lm 830 120° 28W Gold/White Phasecut Ø80cm



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 45

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	50

**PRODUCT DATA SHEET**

Halo Pendant 3200lm 830 120° 28W Gold/White Phasecut Ø80cm

Art.no: 1127-2-120-9

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Lens (Diffuser)	Frosted
Lifetime (h)	L80B10: 50.000
MacAdam (SDCM)	6
UGR (<=)	16
Forward Current LED (min-max) (mA)	6 - 28
Forward Voltage LED (max tp=25) (V)	3.4
Driftspenning LED (min tp=65) (V)	2.6

DIMENSIONS	
Width (product) (mm)	800.0
Height (product) (mm)	34.0

MATERIALS AND SURFACES	
Color	Gold/White

INSTALLATION AND CONNECTION	
Areas of use	Cafe, Hotel, Open access areas, Restaurant, Shop, Showroom
Mounting	Ceiling, Pendant
Connection (system)	1813 Quick connection

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	G
CE mark	Yes