




**PRODUCT DATA SHEET**

Silindir Maxi 3350lm 927 30° 28W BK 3-circuit

Art.no: 1159-7-30-2

*Lighting Solutions*

Silindir Maxi 3350lm 927 30° 28W BK 3-circuit

**A⁺**

Silindir Maxi is the most powerful spotlight in the Silindir-series. With 28W, high light output and CRI it is very suitable for stores and showrooms. The spotlight can be adjusted in all angles to meet every need. Tilttable 90° and 350° rotatable around its own axis. L305mm - Ø85mm

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
CRI / Ra (>=)	90

**PRODUCT DATA SHEET**

Silindir Maxi 3350lm 927 30° 28W BK 3-circuit

Art.no: 1159-7-30-2

*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	2700
Color Code	927
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 60 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic

DRIVER	
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	700 - null
CC (forward voltage driver) (V)	25.0 - 50.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	5.0
Max load pr circuit - B10	14
Max load pr circuit - B16	24
Max load pr circuit - C10	24
Max load pr circuit - C16	40
Inrush current time (μ s)	150.0
Inrush current I _{max} (A)	25.0

DIMENSIONS	
Width (product) (mm)	85.0
Height (product) (mm)	305.0
Weight (product) (kg)	1.3

MATERIALS AND SURFACES	
Color	Black

**PRODUCT DATA SHEET**

Silindir Maxi 3350lm 927 30° 28W BK 3-circuit

Art.no: 1159-7-30-2

*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A+