

**PRODUCT DATA SHEET**

Trimo Mini 3650lm 830 40° 24W WH 18i3

Art.no: 18020-7-40-3

*Lighting Solutions*

Trimo Mini 3650lm 830 40° 24W WH 18i3



Our Trimo range of downlights guarantees a minimum of stray light. This is accomplished by using a recessed LED light source. This model requires a hole dimension of 112mm in diameter making it very versatile providing very powerful light. The Trimo Mini has a 18i3 connector and is supplied with a variety of connector solutions.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	121
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic
Forward Current LED (min-max) (mA)	350 - 1400
Forward Voltage LED (max tp=25) (V)	41.7
Driftspenning LED (min tp=65) (V)	30.2

**PRODUCT DATA SHEET**

Trimo Mini 3650lm 830 40° 24W WH 18i3

Art.no: 18020-7-40-3

*Lighting Solutions*

DRIVER	
Protection Class (driver)	1 or 2
Max Output Voltage (V)	54
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Flicker-free	Yes
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	600 - null
CC (forward voltage driver) (V)	30.0 - 43.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	30.0
Max load pr circuit - B10	55
Max load pr circuit - B16	90
Max load pr circuit - C10	65
Max load pr circuit - C16	100
Inrush current time (μ s)	100.0
Inrush current I _{max} (A)	8.0

DIMENSIONS	
Width (product) (mm)	122.0
Height (product) (mm)	110.0
Weight (product) (kg)	0.7

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Generally, Hotel, Shop
Mounting	Recessed, Ceiling
Connection (system)	18i3 Quick connection

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A



PRODUCT DATA SHEET

Trimo Mini 3650lm 830 40° 24W WH 18i3

Art.no: 18020-7-40-3



Lighting Solutions

ALTERNATIVE DRIVERS

Current Setting (mA) ?

600