



**PRODUCT DATA SHEET**

Linea Extrude 4400lm 840 Opal 38W BK TrackMount  
Art.no: 19037-01-2



*Lighting Solutions*



## Linea Extrude 4400lm 840 Opal 38W BK TrackMount



Linea is a luminaire for indoor use and is designed to be mounted in a wide range of installations. With its slim design and high light output this is a very interesting luminaire that is used in a wide range of retail and commercial installations, demanding a visually good design. The track mounted version is very easy to move around in the premises. Linea Extrude is available in three different colors.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

**PRODUCT DATA SHEET**

Linea Extrude 4400lm 840 Opal 38W BK TrackMount

Art.no: 19037-01-2

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	105
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840
Lightsource Type	LED (built in)
Lens (Diffuser)	Opal
Manufacturer (light source)	Samsung

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	350
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - null
CC (forward voltage driver) (V)	86.0 - 143.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	30.0
Max load pr circuit - B10	35
Max load pr circuit - B16	55
Max load pr circuit - C10	40
Max load pr circuit - C16	60
Inrush current time ( $\mu$ s)	37.0
Inrush current I <sub>max</sub> (A)	5.0

DIMENSIONS	
Length (product) (mm)	1150.0
Width (product) (mm)	80.0
Height (product) (mm)	75.0
Weight (product) (kg)	2550.0

MATERIALS AND SURFACES	
Color	Black



## PRODUCT DATA SHEET

Linea Extrude 4400lm 840 Opal 38W BK TrackMount  
Art.no: 19037-01-2



*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Shop
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++

## LIGHT DISTRIBUTION

