

**PRODUCT DATA SHEET**

Linea Market Recessed 2500lm 830 25W WH 18i3 D.Asym L595mm

Art.no: 19437-04-3



Linea Market Recessed 2500lm 830 25W WH 18i3 D.Asym L595mm

**A++**

Linea Market Recessed is a luminaire designed for recessing in suspended ceiling. The luminaire has double asymmetric lens optics. This allows the luminaire illuminates the shelves of shops in a very good manner. Linea Market Recessed has EPCOM18i3 chassis connector and can be supplied with a variety of different connector options

ELECTRICAL DATA

Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA

IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA

Efficacy (system) (lm/W)	123
CRI / Ra ($\geq$)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Micropris.

DRIVER

Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	250

**PRODUCT DATA SHEET**

Linea Market Recessed 2500lm 830 25W WH 18i3 D.Asym L595mm

Art.no: 19437-04-3

*Lighting Solutions*

DRIVER	
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	250 - 350
CC (forward voltage driver) (V)	51.0 - 109.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	5.0
Max load pr circuit - B10	24
Max load pr circuit - B16	38
Max load pr circuit - C10	40
Max load pr circuit - C16	63
Leakage current (mA)	0.45
Inrush current time (µs)	250.0
Inrush current I _{max} (A)	15.0

DIMENSIONS	
Length (product) (mm)	595.0
Width (product) (mm)	97.0
Height (product) (mm)	59.0
Weight (product) (kg)	3.3

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Connection (system)	Cable 1.2m

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++