

**PRODUCT DATA SHEET**

Pollux Sensor M/S 1600lm 830/840/857 120° 15W WH IP54 Ø250mm
Art.no: 2118-MS-120-3



Lighting Solutions



Pollux Sensor M/S 1600lm 830/840/857 120° 15W WH IP54 Ø250mm



ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	MW RF Master-Slave Dim
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK10
IP (system)	IP54
Outdoor	No
Operating temperature (°C)	-20 - 45

**PRODUCT DATA SHEET**

Pollux Sensor M/S 1600lm 830/840/857 120° 15W WH IP54 Ø250mm

Art.no: 2118-MS-120-3

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3/4/5700
Color Code	830/840/857
Lightsource Type	LED (built in)
Lens (Diffuser)	Opal
Lifetime (h)	L80B10: 100 000

DIMENSIONS	
Height (product) (mm)	50.0
Weight (product) (kg)	0.76
Diameter (product) (mm)	250.0

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9016
Housing Material	Polycarbonate

INSTALLATION AND CONNECTION	
Areas of use	Generally, Hotel, Industrial, Open access areas
Mounting	Surface, Ceiling
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	F
CE mark	Yes