

**PRODUCT DATA SHEET**

Pollux Sensor M/S 2800lm 830/840/857 120° 25W WH IP54 Ø300mm
Art.no: 2119-MS-120-3



Lighting Solutions



Pollux Sensor M/S 2800lm 830/840/857 120° 25W WH IP54 Ø300mm



| ELECTRICAL DATA | |
|---------------------------|------------------------|
| Protection Class (system) | 2 |
| Dimming (system) | MW RF Master-Slave Dim |
| Voltage (system) [V] | 230V 50Hz |

| TECHNICAL DATA | |
|----------------------------|----------|
| IK (system) | IK10 |
| IP (system) | IP54 |
| Outdoor | No |
| Operating temperature (°C) | -20 - 45 |

**PRODUCT DATA SHEET**

Pollux Sensor M/S 2800lm 830/840/857 120° 25W WH IP54 Ø300mm

Art.no: 2119-MS-120-3

*Lighting Solutions*

| PHOTOMETRIC DATA | |
|-----------------------------|-----------------|
| CRI / Ra (>=) | 80 |
| CCT (Color Temperature) (K) | 3/4/5700 |
| Color Code | 830/840/857 |
| Lightsource Type | LED (built in) |
| Lens (Diffuser) | Opal |
| Lifetime (h) | L80B10: 100 000 |

| DRIVER | |
|---------------------|----------------------|
| Dimming output type | Amplitude Modulation |

| DIMENSIONS | |
|-------------------------|-------|
| Height (product) (mm) | 58.0 |
| Weight (product) (kg) | 1.09 |
| Diameter (product) (mm) | 300.0 |

| MATERIALS AND SURFACES | |
|------------------------|---------------|
| Color | White |
| RAL Code | RAL9016 |
| Housing Material | Polycarbonate |

| INSTALLATION AND CONNECTION | |
|-----------------------------|---|
| Areas of use | Generally, Hotel, Industrial, Open access areas |
| Mounting | Surface, Ceiling |
| Connection (system) | QuickConnect |

| ENERGY AND CERTIFICATIONS | |
|---------------------------|-----|
| Energy Class EPREL | F |
| CE mark | Yes |