


**PRODUCT DATA SHEET**

Aludra 390lm 827 70° 3,2W WH 2m cable w/o driver

Art.no: 2172-70-3

*Lighting Solutions*

Aludra 390lm 827 70° 3,2W WH 2m cable w/o driver



LED furniture downlight with latest LED technology, with high lumen output. Perfect as illumination in cabinets recessed or surface mounted together with front ring. Includes 2m cable with quickconnect. Extension cables, connector box and front ring are available as accessories. Connects to 350mA LED driver. Voltage 8,9-9,6V pr luminaire. To be connected in series with connector box. Driver must be calculated with regards to voltage (because in series) and power. Both phasecut and DALI-driver can be used as on/off driver (without dimming). On/ Off driver (LED to be wired in serial): 1-5 pcs Q4-350mA-20W-01 Driver 350mA cc (2-58V) 20W IP20 w/3m cable Euro-plug WH Phasecut driver: 1 pc MINID35004NT Driver 350mA cc 4W (6-12V) Phasecut Mini AcTec 2 pcs D35009NT Driver 350mA 9W (13-26V) Phasecut AcTec 2-5 pcs DIM350MA/18W Driver 350mA cc 18W 15-52V PhaseCut-dim AcTEC 3-4 pcs 87500386 Driver 350mA cc(21-42V) LCBI 15W 350mA Basic Phasecut SR ADV 3-5 pcs D35018NT Driver 350mA 18W (26-52V) Phasecut AcTec DALI driver: 1-5 pcs LCM-25DA Driver 350/500/600/700/900/1050mA cc 25W DALI/Push MeanWell 1-7 pcs 127413 Driver 350-1050mA cc 48V 60W MAXI JOLLY AM/PWM US DALI2 TCI 1-10 pcs LCM-40D Driver 350/500/600/700/900/1050mA cc 40W DALI/Push MeanWell

ELECTRICAL DATA	
Protection Class (system)	3
Dimming (system)	Depending on Driver

TECHNICAL DATA	
IP (system)	IP44
Outdoor	No

**PRODUCT DATA SHEET**

Aludra 390lm 827 70° 3,2W WH 2m cable w/o driver

Art.no: 2172-70-3

*Lighting Solutions*

TECHNICAL DATA	
Operating temperature (°C)	-20 - 40

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	122
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	2700
Color Code	827
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B50: 40 000
MacAdam (SDCM)	3
Manufacturer (light source)	Bridgelux
Forward Voltage LED (max tp=25) (V)	9.6
Driftspenning LED (min tp=65) (V)	8.9

DIMENSIONS	
Width (product) (mm)	70.0
Height (product) (mm)	17.0
Weight (product) (kg)	0.1

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Kitchen, Residence, Staircase
Mounting	Recessed, Floor, Furnishings, Furniture
Connection (system)	Mini connector 2m

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++



PRODUCT DATA SHEET

Aludra 390lm 827 70° 3,2W WH 2m cable w/o driver

Art.no: 2172-70-3



Lighting Solutions

LIGHT DISTRIBUTION

