

**PRODUCT DATA SHEET**

Rigil 900lm 830 360° 15W Quickconnect Dark Grey  
Art.no: 2475-36-7



*Lighting Solutions*



## Rigil 900lm 830 360° 15W Quickconnect Dark Grey



A

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK10
IP (system)	IP54
Outdoor	Yes
Operating temperature (°C)	-20 - 30

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	59
CRI / Ra (>=)	80

**PRODUCT DATA SHEET**

Rigil 900lm 830 360° 15W Quickconnect Dark Grey

Art.no: 2475-36-7

*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	50 000
Forward Voltage LED (max tp=25) (V)	50.0
Driftspenning LED (min tp=65) (V)	45.0

DRIVER	
Protection Class (driver)	2
IP (driver)	IP65
Expected Lifetime (driver) (h)	30000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	250 - null
CC (forward voltage driver) (V)	36.0 - 48.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	180.0
Max load pr circuit - B10	17
Max load pr circuit - B16	26
Max load pr circuit - C10	29
Max load pr circuit - C16	47
Leakage current (mA)	0.5
Inrush current time (µs)	125.0
Inrush current I <sub>max</sub> (A)	15.0

DIMENSIONS	
Width (product) (mm)	120.0
Height (product) (mm)	800.0
Weight (product) (kg)	2.4

MATERIALS AND SURFACES	
Color	Antracite
RAL Code	RAL7024
Housing Material	Aluminium



## PRODUCT DATA SHEET

Rigil 900lm 830 360° 15W Quickconnect Dark Grey

Art.no: 2475-36-7



*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Generally, Outdoor, Residence
Mounting	Ground, Bollard
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A

## LIGHT DISTRIBUTION

