

**PRODUCT DATA SHEET**

Driver 350-1050mA cc LCA 75W 350-1050mA one4all Ip PRE DALI

Art.no: 28000659

*Lighting Solutions*

Driver 350-1050mA cc LCA 75W 350-1050mA one4all Ip PRE DALI

Forward voltage is dependent of current setting. See manufacture datasheet for complete details.

ELECTRICAL DATA	
Voltage (system) [V]	230V 50Hz / 176-275VDC

TECHNICAL DATA	
Operating temperature (°C)	-25 - 50

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	250
Dimming (driver)	Corridor, DALI2, Push, Ready2Mains
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000

**PRODUCT DATA SHEET**

Driver 350-1050mA cc LCA 75W 350-1050mA one4all Ip PRE DALI
Art.no: 28000659



Lighting Solutions

DRIVER	
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	350 - 1050
Current setting (driver)	DALI-2, I-Select 2 Plug (Tridonic), Ready2Mains
CC (forward voltage driver) (V)	40.0 - 110.0
Output Current Tolerance (%)	3.0
Current Ripple (%)	2.5
Max load pr circuit - B10	9
Max load pr circuit - B16	14
Max load pr circuit - C10	15
Max load pr circuit - C16	23
Leakage current (mA)	0.65
Inrush current time (μ s)	178.0
Inrush current I _{max} (A)	40.0

DIMENSIONS	
Length (product) (mm)	360.0
Width (product) (mm)	30.0
Height (product) (mm)	21.0
Weight (product) (kg)	0.3