


**PRODUKTDATABLAD**

CBU Driver 350-1050mA cc 38W Bluetooth bDW SR TW 2-ch

Art.no: 28002584

*Lighting Solutions*

CBU Driver 350-1050mA cc 38W Bluetooth bDW SR TW 2-ch

DRIVER / BALLAST	
Produsent (driver)	Tridonic
Produsentens driverbeskrivelse	LC 38W 350-1050mA bDW TW SR PRE2
Effekt (driver) (W)	38
Beskyttelsesklasse (driver)	1 or 2
Maks utgangsspenning (V)	60
Dimmefunksjon (driver)	Casambi, CLO
IP-klasse (driver)	IP20
Forventet levetid (driver) (t)	100000
Konstant strøm eller spenning (CC eller CV)	CC
Konstant strøm (CC driver) (mA)	350 - 1050
Strøminnstilling (driver)	CLO, I-Select 2 Plug (Tridonic)
Konstant strøm (CC driftspenning driver) (V)	20.0 - 50.0
Utgangsstrøm toleranse (%)	3.0
Strømkrusning (%)	2.0
Maks belastning per kurs - B10	10
Maks belastning per kurs - B16	16

**PRODUKTDATABLAD**

CBU Driver 350-1050mA cc 38W Bluetooth bDW SR TW 2-ch

Art.no: 28002584

*Lighting Solutions*

DRIVER / BALLAST	
Maks belastning per kurs - C10	16
Maks belastning per kurs - C16	26
Lekkasjestrøm (mA)	0.5
Startstrøm tid (μ s)	224.0
Startstrøm I _{max} (A)	26.0