



**PRODUCT DATA SHEET**

Seta LED 35W 20° 925 Food WW WH Ø170 18i3

Art.no: 30241-20-3

*Lighting Solutions*

170mm



## Seta LED 35W 20° 925 Food WW WH Ø170 18i3



Seta is the clear choice when one wants recessed spot lighting. This favorite can be found in stores throughout the Nordic region. Thanks to large adjustment possibilities Seta is without doubt one of the best in its class. Seta has 18i3 connector and can be supplied with a variety of connector options. The luminaire is available in three different colors.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	0

**PRODUCT DATA SHEET**

Seta LED 35W 20° 925 Food WW WH Ø170 18i3

Art.no: 30241-20-3

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	Fresh Food
Color Code	Fresh Food
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Manufacturer (light source)	Tridonic

DRIVER	
Manufacturer (driver)	Philips
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	800 - null
CC (forward voltage driver) (V)	25.0 - 45.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	5.0
Max load pr circuit - B10	14
Max load pr circuit - B16	24
Max load pr circuit - C10	24
Max load pr circuit - C16	40
Inrush current time (µs)	150.0
Inrush current I <sub>max</sub> (A)	25.0

DIMENSIONS	
Length (product) (mm)	192.0
Width (product) (mm)	182.0
Height (product) (mm)	136.0

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Shop, Showroom

**PRODUCT DATA SHEET**

Seta LED 35W 20° 925 Food WW WH Ø170 18i3

Art.no: 30241-20-3

*Lighting Solutions*

INSTALLATION AND CONNECTION	
Mounting	Recessed, Ceiling
Connection (system)	18i3 Quick connection

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A

ALTERNATIVE DRIVERS	
Current Setting (mA) ?	800