



**PRODUCT DATA SHEET**

Seta 5450lm 940 30° 41W WH 18i5 DALI

Art.no: 30246-7-30-3-ddd

*Lighting Solutions*

170mm



Seta 5450lm 940 30° 41W WH 18i5 DALI



Seta is the clear choice when one wants recessed spot lighting. This favorite can be found in stores throughout the Nordic region. Thanks to large adjustment possibilities Seta is without doubt one of the best in its class. Seta has 18i3 connector and can be supplied with a variety of connector options. The luminaire is available in three different colors.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	DALI
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
CRI / Ra (>=)	90

**PRODUCT DATA SHEET**

Seta 5450lm 940 30° 41W WH 18i5 DALI

Art.no: 30246-7-30-3-ddd

*Lighting Solutions*

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	4000
Color Code	940
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Manufacturer (light source)	Tridonic

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Standby power P_{sb} (W) <	0.15
Flicker metric (Pst LM) <	1.0
Stroboscopic effect metric (SVM) <	0.4
Max Output Voltage (V)	60
Dimming (driver)	CLO, Corridor, DALI2, Push, Ready2Mains
Dimming Minimum Level (%)	1.0
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	500 - 1400
Current setting (driver)	DALI-2, I-Select 2 Plug (Tridonic), Ready2Mains
CC (forward voltage driver) (V)	25.0 - 49.9
Output Current Tolerance (%)	3.0
Current Ripple (%)	2.0
Max load pr circuit - B10	14
Max load pr circuit - B16	23
Max load pr circuit - C10	23
Max load pr circuit - C16	38
Leakage current (mA)	0.16
Inrush current time (μ s)	200.0
Inrush current I_{max} (A)	23.0

DIMENSIONS	
Length (product) (mm)	192.0
Width (product) (mm)	182.0

**PRODUCT DATA SHEET**

Seta 5450lm 940 30° 41W WH 18i5 DALI

Art.no: 30246-7-30-3-ddd

*Lighting Solutions***DIMENSIONS**

Height (product) (mm)	136.0
-----------------------	-------

MATERIALS AND SURFACES

Color	White
-------	-------

INSTALLATION AND CONNECTION

Areas of use	Shop, Showroom
Mounting	Recessed, Ceiling
Connection (system)	18i5 DALI Quick connection

ENERGY AND CERTIFICATIONS

CE mark	Yes
Energy Efficiency Class	A++ - A

ALTERNATIVE DRIVERS

Current Setting (mA) ?	800
------------------------	-----