



**PRODUCT DATA SHEET**

Seta Mini 2200lm FreshFood 824 30° 28W WH 18i3 Ø140mm

Art.no: 30326-6-30-3

*Lighting Solutions*

140mm



## Seta Mini 2200lm FreshFood 824 30° 28W WH 18i3 Ø140mm



Seta Mini is a small and very flexible LED downlight offering great number of adjustment possibilities. The Seta Mini is supplied with a cable connector type 18i3- and can be delivered with a variety of connector options. The downlight is available in three different colors and with a wide range of reflectors. Rotatable 350° and tiltable 70°.

ELECTRICAL DATA	
Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

**PRODUCT DATA SHEET**

Seta Mini 2200lm FreshFood 824 30° 28W WH 18i3 Ø140mm

Art.no: 30326-6-30-3

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	74
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	Fresh Food
Color Code	Fresh Food
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	4
UGR (<=)	15
Manufacturer (light source)	Tridonic
Forward Current LED (min-max) (mA)	350 - 1400
Forward Voltage LED (max tp=25) (V)	41.7
Driftspenning LED (min tp=65) (V)	30.2

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1 or 2
Max Output Voltage (V)	60
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	700 - null
Current setting (driver)	None
CC (forward voltage driver) (V)	25.0 - 50.0
Output Current Tolerance (%)	7.5
Current Ripple (%)	5.0
Max load pr circuit - B10	14
Max load pr circuit - B16	24
Max load pr circuit - C10	24
Max load pr circuit - C16	40
Inrush current time (µs)	150.0
Inrush current I <sub>max</sub> (A)	25.0



## PRODUCT DATA SHEET

Seta Mini 2200lm FreshFood 824 30° 28W WH 18i3 Ø140mm  
Art.no: 30326-6-30-3



*Lighting Solutions*

DIMENSIONS	
Length (product) (mm)	150.0
Width (product) (mm)	150.0
Height (product) (mm)	112.0
Weight (product) (kg)	0.95

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Shop, Showroom
Mounting	Recessed, Ceiling
Connection (system)	18i3 Quick connection

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A

ALTERNATIVE DRIVERS	
Current Setting (mA) ?	700

## LIGHT DISTRIBUTION

