




**PRODUCT DATA SHEET**

Silindir Maxi Short 3530lm 930 20° 28W BK 3-circuit DALI

Art.no: 3403-7-20-2-ddd

*Lighting Solutions*

Silindir Maxi Short 3530lm 930 20° 28W BK 3-circuit DALI



| ELECTRICAL DATA | |
|---------------------------|-----------|
| Protection Class (system) | 1 |
| Dimming (system) | DALI2 |
| Voltage (system) [V] | 230V 50Hz |

| TECHNICAL DATA | |
|----------------|------|
| IP (system) | IP20 |
| Outdoor | No |

| PHOTOMETRIC DATA | |
|-----------------------------|------|
| Efficacy (system) (lm/W) | 114 |
| CRI / Ra (>=) | 90 |
| CCT (Color Temperature) (K) | 3000 |
| Color Code | 930 |

**PRODUCT DATA SHEET**

Silindir Maxi Short 3530lm 930 20° 28W BK 3-circuit DALI

Art.no: 3403-7-20-2-ddd

*Lighting Solutions*

| PHOTOMETRIC DATA | |
|-------------------------------------|-----------------|
| Lens (Diffuser) | Clear |
| Lifetime (h) | L80B10: 100 000 |
| MacAdam (SDCM) | 3 |
| Manufacturer (light source) | Tridonic |
| Forward Current LED (min-max) (mA) | null - 1540 |
| Forward Voltage LED (max tp=25) (V) | 38.7 |
| Driftspenning LED (min tp=65) (V) | 29.3 |

| DRIVER | |
|--|----------------------|
| Manufacturer (driver) | Tridonic |
| Protection Class (driver) | 2 |
| Max Output Voltage (V) | 60 |
| Dimming Minimum Level (%) | 1.0 |
| Dimming output type | Amplitude Modulation |
| IP (driver) | IP20 |
| Expected Lifetime (driver) (h) | 100000 |
| Constant current or voltage (CC or CV) | CC |
| CC (driver) [mA] | 500 - 1050 |
| CC (forward voltage driver) (V) | 14.0 - 42.0 |
| Output Current Tolerance (%) | 5.0 |
| Current Ripple (%) | 3.0 |
| Max load pr circuit - B10 | 40 |
| Max load pr circuit - B16 | 64 |
| Max load pr circuit - C10 | 40 |
| Max load pr circuit - C16 | 64 |
| Max load pr circuit - C20 | 80 |
| Leakage current (mA) | 0.7 |
| Inrush current time (µs) | 32.0 |
| Inrush current I _{max} (A) | 9.6 |

| DIMENSIONS | |
|-----------------------|-------|
| Length (product) (mm) | 166.0 |
| Width (product) (mm) | 85.0 |
| Weight (product) (kg) | 1.0 |



PRODUCT DATA SHEET

Silindir Maxi Short 3530lm 930 20° 28W BK 3-circuit DALI

Art.no: 3403-7-20-2-ddd



Lighting Solutions

MATERIALS AND SURFACES

| | |
|-------|-------|
| Color | Black |
|-------|-------|

INSTALLATION AND CONNECTION

| | |
|---------------------|---------------------|
| Areas of use | Shop, Showroom |
| Mounting | Track, Ceiling |
| Connection (system) | Track 3-Circuit+dim |

ENERGY AND CERTIFICATIONS

| | |
|-------------------------|---------|
| CE mark | Yes |
| Energy Efficiency Class | A++ - A |

LIGHT DISTRIBUTION

