




**PRODUCT DATA SHEET**

Silindir Maxi Short 3530lm 930 30° 28W WH 3-circuit DALI
Art.no: 3403-7-30-3-ddd



Lighting Solutions



Silindir Maxi Short 3530lm 930 30° 28W WH 3-circuit DALI



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI2
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	108
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000
Color Code	930

**PRODUCT DATA SHEET**

Silindir Maxi Short 3530lm 930 30° 28W WH 3-circuit DALI

Art.no: 3403-7-30-3-ddd

*Lighting Solutions*

PHOTOMETRIC DATA	
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic
Forward Current LED (min-max) (mA)	null - 1540
Forward Voltage LED (max tp=25) (V)	38.7
Driftspenning LED (min tp=65) (V)	29.3

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	2
Max Output Voltage (V)	60
Dimming Minimum Level (%)	1.0
Dimming output type	Amplitude Modulation
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	500 - 1050
Output Current Tolerance (%)	5.0
Current Ripple (%)	3.0
Max load pr circuit - B10	40
Max load pr circuit - B16	64
Max load pr circuit - C10	40
Max load pr circuit - C16	64
Max load pr circuit - C20	80
Leakage current (mA)	0.7
Inrush current time (μ s)	32.0
Inrush current I _{max} (A)	9.6

DIMENSIONS	
Length (product) (mm)	166.0
Width (product) (mm)	85.0
Weight (product) (kg)	1.0

**PRODUCT DATA SHEET**

Silindir Maxi Short 3530lm 930 30° 28W WH 3-circuit DALI

Art.no: 3403-7-30-3-ddd

*Lighting Solutions*

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit+dim

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++ - A

LIGHT DISTRIBUTION