

**PRODUCT DATA SHEET**

Kappa Round 950lm 930 8,9W 48° Phasecut WH/WH

Art.no: 3521-48-3

*Lighting Solutions*

## Kappa Round 950lm 930 8,9W 48° Phasecut WH/WH



ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Phase-Cut
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No

PHOTOMETRIC DATA	
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000
Color Code	930
Lightsource Type	LED (built in)

**PRODUCT DATA SHEET**

Kappa Round 950lm 930 8,9W 48° Phasecut WH/WH

Art.no: 3521-48-3

*Lighting Solutions*

PHOTOMETRIC DATA	
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000

DRIVER	
Manufacturer (driver)	AcTEC
Protection Class (driver)	2
Max Output Voltage (V)	18
Dimming (driver)	Phase-Cut
Dimming Minimum Level (%)	1.0
Dimming Phasecut Type	Leading / Trailing edge
IP (driver)	IP20
Expected Lifetime (driver) (h)	30000
CC (driver) [mA]	500 - null
CC (forward voltage driver) (V)	9.0 - 18.0
Output Current Tolerance (%)	5.0
Current Ripple (%)	5.0
Max load pr circuit - B10	35
Max load pr circuit - B16	56
Max load pr circuit - C10	74
Max load pr circuit - C16	118
Leakage current (mA)	5.0
Inrush current time (µs)	300.0
Inrush current I <sub>max</sub> (A)	5.0

DIMENSIONS	
Width (product) (mm)	85.0
Height (product) (mm)	93.0

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Cottage, Generally, Hotel, Kitchen, Residence, Restaurant
Mounting	Surface, Ceiling



**PRODUCT DATA SHEET**

Kappa Round 950lm 930 8,9W 48° Phasecut WH/WH

Art.no: 3521-48-3



*Lighting Solutions*

**INSTALLATION AND CONNECTION**

Connection (system)	Terminal
---------------------	----------

**ENERGY AND CERTIFICATIONS**

CE mark	Yes
Energy Efficiency Class	A++ - A

**LIGHT DISTRIBUTION**

