


**PRODUCT DATA SHEET**

Tania Mini 1450lm 927 36° 14,5W 3-circuit BK DALI
 Art.no: 3551-36-2-ddd

*Lighting Solutions*

Tania Mini 1450lm 927 36° 14,5W 3-circuit BK DALI



Tania Mini DALI2 is a small spotlight in a contemporary design. Perfect for use at home and in other commercial settings. Front ring is sold separately. This version is with LED COB and no changeable lightbulb.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI2
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-20 - 40

PHOTOMETRIC DATA	
CRI / Ra (>=)	90

**PRODUCT DATA SHEET**

Tania Mini 1450lm 927 36° 14,5W 3-circuit BK DALI
Art.no: 3551-36-2-ddd



Lighting Solutions

PHOTOMETRIC DATA	
CCT (Color Temperature) (K)	2700
Color Code	927
Lightsource Type	LED (built in)
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 55 000
MacAdam (SDCM)	3
Manufacturer (light source)	Bridgelux

DIMENSIONS	
Length (product) (mm)	167.0
Weight (product) (kg)	0.5
Diameter (product) (mm)	60.0

MATERIALS AND SURFACES	
Color	Black
Housing Material	Aluminium

INSTALLATION AND CONNECTION	
Areas of use	Cafe, Cottage, Generally, Hotel, Residence, Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit+dim

ENERGY AND CERTIFICATIONS	
Energy Class EPREL	E
CE mark	Yes
EPD number	NEPD-14536-15051
Energy Efficiency Class	A++ - A



PRODUCT DATA SHEET

Tania Mini 1450lm 927 36° 14,5W 3-circuit BK DALI
Art.no: 3551-36-2-ddd



Lighting Solutions

LIGHT DISTRIBUTION

