NORLUX®
Lighting Solutions

580mm

59 mm

66 mm

Pluto Sensor 900lm 9W 830 130° WH w/Socket Quickconnect

CE ⏚ 230V 50Hz IP44 IK06 ⌂

A⁺⁺ – A F ᴬ↑ᴳ

Pluto Sensor is a highly efficient bathroom wall light. With IP44 it`s safe for use in bathrooms. With microwave sensor, socket and quickconnect for easy installation.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	Sensor (MW)
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK06
IP (system)	IP44
Outdoor	No
Operating temperature (°C)	-20 - 45

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	100
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	3000
Color Code	830
Socket / Cap-Base	N/A
Lens (Diffuser)	Opal
Lifetime (h)	L80B50: 50 000

DRIVER	
Dimming output type	Amplitude Modulation
CC (driver) [mA]	81 - null
Output Current Tolerance (%)	10.0
Max load pr circuit - B10	35
Max load pr circuit - B16	56
Max load pr circuit - C10	74
Max load pr circuit - C16	118

DIMENSIONS	
Length (product) (mm)	580.0
Width (product) (mm)	59.0
Heigth (product) (mm)	66.0
Weight (product) (kg)	0.66

MATERIALS AND SURFACES	
Color	White
RAL Code	RAL9016

INSTALLATION AND CONNECTION	
Areas of use	Bathroom, Cottage, Generally, Residence
Mounting	Surface, Wall
Connection (system)	QuickConnect

ENERGY AND CERTIFICATIONS

Energy Class EPREL	F
CE mark	Yes
Energy Efficiency Class	A++ - A