


**PRODUCT DATA SHEET**

Columba 21000lm 840 90° 115W WH DALI

Art.no: 5713-04-3-ddd

*Lighting Solutions*

## Columba 21000lm 840 90° 115W WH DALI



Surface mounted or suspended LED luminaire for use in industry, warehouse, hall and sports arena. Choose between various editions with different lumen output, optics and DALI2 driver.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP65
Outdoor	No
Operating temperature (°C)	-20 - 35

**PRODUCT DATA SHEET**

Columba 21000lm 840 90° 115W WH DALI

Art.no: 5713-04-3-ddd

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	172
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840
Socket / Cap-Base	N/A
Lifetime (h)	L80B50: 100 000
MacAdam (SDCM)	3

DRIVER	
Manufacturer (driver)	Tridonic
Protection Class (driver)	1
Max Output Voltage (V)	350
IP (driver)	IP20
Expected Lifetime (driver) (h)	100000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	325 - 1050
CC (forward voltage driver) (V)	80.0 - 143.0
Output Current Tolerance (%)	3.0
Current Ripple (%)	2.0
Max load pr circuit - B10	17
Max load pr circuit - B16	22
Max load pr circuit - C10	28
Max load pr circuit - C16	36
Leakage current (mA)	0.25
Inrush current time (µs)	162.0
Inrush current I <sub>max</sub> (A)	17.7

DIMENSIONS	
Length (product) (mm)	1444.0
Width (product) (mm)	114.0
Height (product) (mm)	80.0
Weight (product) (kg)	2.8

MATERIALS AND SURFACES	
Color	White



**PRODUCT DATA SHEET**

Columba 21000lm 840 90° 115W WH DALI

Art.no: 5713-04-3-ddd



*Lighting Solutions*

INSTALLATION AND CONNECTION	
Areas of use	Generally, Industrial, Sports areas
Mounting	Surface, Suspended, Ceiling

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++

**LIGHT DISTRIBUTION**

