


**PRODUCT DATA SHEET**

Columba 31500lm 840 90° 172W WH DALI

Art.no: 5714-04-3-ddd

*Lighting Solutions*

## Columba 31500lm 840 90° 172W WH DALI



Surface mounted or suspended LED luminaire for use in industry, warehouse, hall and sports arena. Choose between various editions with different lumen output, optics and DALI2 driver.

ELECTRICAL DATA	
Protection Class (system)	1
Dimming (system)	DALI
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IK (system)	IK08
IP (system)	IP65
Outdoor	No
Operating temperature (°C)	-20 - 35

**PRODUCT DATA SHEET**

Columba 31500lm 840 90° 172W WH DALI

Art.no: 5714-04-3-ddd

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	172
CRI / Ra (>=)	80
CCT (Color Temperature) (K)	4000
Color Code	840
Socket / Cap-Base	N/A
Lifetime (h)	L80B50: 100 000
MacAdam (SDCM)	3

DIMENSIONS	
Length (product) (mm)	1953.0
Width (product) (mm)	114.0
Height (product) (mm)	80.0
Weight (product) (kg)	4.1

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Generally, Industrial, Sports areas
Mounting	Surface, Suspended, Ceiling

ENERGY AND CERTIFICATIONS	
CE mark	Yes
Energy Efficiency Class	A++



**PRODUCT DATA SHEET**

Columba 31500lm 840 90° 172W WH DALI

Art.no: 5714-04-3-ddd



*Lighting Solutions*

**LIGHT DISTRIBUTION**

