


**PRODUCT DATA SHEET**

Leila C Midi 2100lm 930 67° 16W w/o driver cut out Ø165mm WH

Art.no: 6921-67-3

*Lighting Solutions*

Ø 165mm



Leila C Midi 2100lm 930 67° 16W w/o driver cut out Ø165mm WH



Leila C Midi is a highly efficient downlight with 126 lm/W. With wide beam angle and rotationally symmetric light distribution, it's suitable for all place that requires high lumen output. Can be delivered with on / off, phasecut or DALI2 driver. See accessories for suitable driver.

ELECTRICAL DATA	
Protection Class (system)	3
Dimming (system)	Depending on Driver
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA	
IP (system)	IP20
Outdoor	No
Operating temperature (°C)	-25 - 50

**PRODUCT DATA SHEET**

Leila C Midi 2100lm 930 67° 16W w/o driver cut out Ø165mm WH

Art.no: 6921-67-3

*Lighting Solutions*

PHOTOMETRIC DATA	
CRI / Ra (>=)	90
CCT (Color Temperature) (K)	3000
Color Code	930
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic
Forward Current LED (min-max) (mA)	null - 1540
Forward Voltage LED (max tp=25) (V)	38.7
Driftspenning LED (min tp=65) (V)	29.3

DIMENSIONS	
Width (product) (mm)	180.0
Height (product) (mm)	120.0
Weight (product) (kg)	1.1

MATERIALS AND SURFACES	
Color	White

INSTALLATION AND CONNECTION	
Areas of use	Generally, Hotel, Office, School, Showroom
Mounting	Recessed, Ceiling
Connection (system)	Depending on driver

ENERGY AND CERTIFICATIONS	
CE mark	Yes
EPD number	NEPD-14106-14439
Energy Efficiency Class	A++ - A