



**PRODUCT DATA SHEET**

Lobus 4050lm 930 20° 30W BK 3-Circuit BI

Art.no: 7012-7-20-2

*Lighting Solutions*

Lobus 4050lm 930 20° 30W BK 3-Circuit BI



Lobus is a small and elegant spotlight for use in track lighting systems. This spotlight has very high lumen output per watt and this puts it in the top segment. The Lobus is very flexible, offering numerous adjustment possibilities making it easy to achieve the perfect light design in stores. The Lobus is available with three different reflectors and comes in three different colors.

ELECTRICAL DATA

Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA

IP (system)	IP20
Outdoor	No
Operating temperature (°C)	0 - 35

**PRODUCT DATA SHEET**

Lobus 4050lm 930 20° 30W BK 3-Circuit BI

Art.no: 7012-7-20-2

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	127
CRI / Ra ($\geq$)	90
CCT (Color Temperature) (K)	3000
Color Code	930
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic
Forward Current LED (min-max) (mA)	null - 1540
Forward Voltage LED (max $t_p=25$) (V)	38.7
Driftspenning LED (min $t_p=65$) (V)	29.3

DRIVER	
Protection Class (driver)	2
Max Output Voltage (V)	59
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	525 - 900
CC (forward voltage driver) (V)	20.0 - 40.0
Output Current Tolerance (%)	5.0
Max load pr circuit - B10	30
Max load pr circuit - B16	50
Max load pr circuit - C10	50
Max load pr circuit - C16	85
Inrush current time (μ s)	50.0
Inrush current I _{max} (A)	5.0

DIMENSIONS	
Length (product) (mm)	228.0
Width (product) (mm)	97.0
Height (product) (mm)	180.0
Weight (product) (kg)	0.841

**PRODUCT DATA SHEET**

Lobus 4050lm 930 20° 30W BK 3-Circuit BI

Art.no: 7012-7-20-2

*Lighting Solutions***MATERIALS AND SURFACES**

Color	Black
Housing Material	Aluminium

INSTALLATION AND CONNECTION

Areas of use	Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS

CE mark	Yes
EPD number	NEPD-12068-12061
Energy Efficiency Class	A++ - A

LIGHT DISTRIBUTION