





PRODUCT DATA SHEET

Lobus FreshFood 2600lm 824 30° 30W WH 3-Circuit BI

Art.no: 7016-7-30-3



Lighting Solutions



Lobus FreshFood 2600lm 824 30° 30W WH 3-Circuit BI



Lobus is a small and elegant spotlight for use in track lighting systems. This spotlight has very high lumen output per watt and this puts it in the top segment. The Lobus is very flexible, offering numerous adjustment possibilities making it easy to achieve the perfect light design in stores. The Lobus is available with three different reflectors and comes in three different colors.

ELECTRICAL DATA

Protection Class (system)	2
Dimming (system)	None
Voltage (system) [V]	230V 50Hz

TECHNICAL DATA

IP (system)	IP20
Outdoor	No
Operating temperature (°C)	0 - 35

**PRODUCT DATA SHEET**

Lobus FreshFood 2600lm 824 30° 30W WH 3-Circuit BI

Art.no: 7016-7-30-3

*Lighting Solutions*

PHOTOMETRIC DATA	
Efficacy (system) (lm/W)	78
CRI / Ra ($\geq$)	80
Lightsource Type	LED (built in)
Socket / Cap-Base	N/A
Lens (Diffuser)	Clear
Lifetime (h)	L80B10: 100 000
MacAdam (SDCM)	3
Manufacturer (light source)	Tridonic
Forward Current LED (min-max) (mA)	500 - 1400
Forward Voltage LED (max $t_p=25$) (V)	36.3
Driftspenning LED (min $t_p=65$) (V)	33.3

DRIVER	
Protection Class (driver)	2
Max Output Voltage (V)	59
IP (driver)	IP20
Expected Lifetime (driver) (h)	50000
Constant current or voltage (CC or CV)	CC
CC (driver) [mA]	525 - 900
CC (forward voltage driver) (V)	20.0 - 40.0
Output Current Tolerance (%)	5.0
Max load pr circuit - B10	30
Max load pr circuit - B16	50
Max load pr circuit - C10	50
Max load pr circuit - C16	85
Inrush current time (μ s)	50.0
Inrush current I _{max} (A)	5.0

DIMENSIONS	
Length (product) (mm)	228.0
Width (product) (mm)	97.0
Height (product) (mm)	180.0
Weight (product) (kg)	0.841



PRODUCT DATA SHEET

Lobus FreshFood 2600lm 824 30° 30W WH 3-Circuit BI

Art.no: 7016-7-30-3



Lighting Solutions

MATERIALS AND SURFACES

Color	White
Housing Material	Aluminium

INSTALLATION AND CONNECTION

Areas of use	Shop, Showroom
Mounting	Track, Ceiling
Connection (system)	Track 3-Circuit

ENERGY AND CERTIFICATIONS

CE mark	Yes
EPD number	NEPD-12068-12061
Energy Efficiency Class	A++ - A

LIGHT DISTRIBUTION

